

# STAR Technology

FORMULATING • INNOVATIVE • SOLUTIONS

## ReleasEze II GA-109-2 Masking Compound

### DESCRIPTION

ReleasEze2 is a simple and effective wipe-on masking compound which may be used with 100 % Epoxy and Water Base Epoxy, Dip & Bake and VPI impregnation processes. ReleasEze2 can be used to prevent the adhesion of varnish to machined surfaces such as shafts, threaded bars and drilled & tapped holes. ReleasEze2 is effective at temperatures up to 300 °C.

### BENEFITS

Mechanical Stability      Oxidation/Corrosion Resistant      Excellent Temperature Stability

### TYPICAL PROPERTIES

Specific Gravity (g/cc):  
Texture:  
Color:

### TEST METHOD

ASTM D1475

### VALUE

0.91  
Smooth  
Green

Shelf Life (months):

36

### APPLICATION PROCEDURES

Apply GA-109-2 by hand, brush or cloth to all surfaces requiring masking. Use 2-3 mm of film build for best results. Process the component until fully cured. Once component has cooled to ambient temperature, simply wipe the masking off with a cloth.

### PRECAUTIONS

For industrial use only. Keep away from children.

Refer to the Material Safety Data Sheets (MSDS forms) pertaining to this product before using.

Avoid contact with skin or eyes. In the event of an eye splash or contact, immediately flush with cold water for 15 minutes and contact a physician. If skin contact occurs, wash with mild soap and water. The wearing of safety glasses with side shields and impervious gloves is recommended.

To the best of our knowledge, the information contained herein is accurate. However, STAR TECHNOLOGY, Inc., does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any material is the sole responsibility of the user. The information contained herein is considered typical properties and is not intended to be used as specifications for our products. This information is offered solely to assist purchaser in selecting the appropriate products for purchaser's own testing. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein and in the material safety data sheet, we cannot guarantee that these are the only hazards that exist. Repeated and prolonged exposure to epoxy resins can cause sensitization or other allergic responses.