

## ReleasEze Natural HA-41-1 Masking Compound

### DESCRIPTION

ReleasEze Natural is the unpigmented version of ReleasEze II, which is a simple and effective wipe-on masking compound used with 100 % Epoxy and Water Base Epoxy, Dip & Bake and VPI impregnation processes. ReleasEze Natural can be used to prevent the adhesion of varnish to machined surfaces such as shafts, threaded bars and drilled & tapped holes. ReleasEze Natural is effective at temperatures up to 300 °C.

### BENEFITS

Mechanical Stability      Oxidation/Corrosion Resistant      Excellent Temperature Stability

### TYPICAL PROPERTIES

Specific Gravity (g/cc):  
Texture:  
Color:

### TEST METHOD

ASTM D1475

### VALUE

0.91  
Smooth  
Amber

Shelf Life (months):

36

### APPLICATION PROCEDURES

Apply ReleasEze Natural by hand, brush or cloth to all surfaces requiring masking. Use 2-3 mm of film build for best results. Process the component until fully cured. Once component has cooled to ambient temperature, simply wipe the masking off with a cloth.

### PRECAUTIONS

For industrial use only. Keep away from children.

Refer to the Material Safety Data Sheets (MSDS forms) pertaining to this product before using.

Avoid contact with skin or eyes. In the event of an eye splash or contact, immediately flush with cold water for 15 minutes and contact a physician. If skin contact occurs, wash with mild soap and water. The wearing of safety glasses with side shields and impervious gloves is recommended.