

STAR Technology

FORMULATING • INNOVATIVE • SOLUTIONS

ER2109

Two Part Epoxy Adhesive

DESCRIPTION

ER2109 is an aggressive yet easy to mix two-part thixotropic epoxy adhesive made for adhesion to a variety of substrates. ER2109 can be mixed in ratios of from 2:1 to 1:1 by weight or by volume and still deliver outstanding adhesive strength and chemical resistance. ER2109 will adhere to most metals, wood, Styrofoam, glass, most engineering plastics and many surface treated polyolifins. Because of the slow gel time and simple mix ratios, ER2109 lends itself to a variety of manual and automated dispense possibilities. Viscosity may be thixod for vertical and non-sag applications. The 2:1 mix ratio gives higher lap shears, higher tensile strength and lower elongation values. Complies with FDA 21 CFR 175.300, 21 CFR 176.170, and 21 CFR 175.105.

Data contained herein are believed to be reliable. Fit-for-use testing should be conducted by each user.

TYPICAL PROPERTIES

	<u>TEST METHOD</u>	<u>VALUE</u>
Gel time (hours):	ASTM D2471	
100 Gram Mass at 75°F:		2 - 3
Thin Film at 75°F:		5 - 9
Full Cure Time at 75°F (hours):		16
Part A:		
Viscosity (cps):	ASTM D2393	12000
Color:		Clear
Part B:		
Viscosity (cps):	ASTM D2393	4000
Color:		Amber
Mixed Product:		
Viscosity (cps):		See Chart Below
Color:		Amber
Tg (°C):	ASTM D3418	
1:1 Mix Ratio:		65
2:1 Mix Ratio:		96
1:1 MIX RATIO PROPERTIES		
Lap Shear [CRS to CRS] (psi):	ASTM D1002	1800
Tensile Strength (psi):	ASTM D638	6400
Elongation at Break (%):		3.8
Compressive strength (psi):		11400
Flexural Modulus (psi):		3.26x10 ⁷
Coefficient of Thermal Expansion (unit/ unit /°C):		5x10 ⁻⁵
Maximum Service Temperature (°F):		500 [Intermittent]

GEL TIME, HARDNESS AND MIXED VISCOSITY AT VARIOUS MIX RATIOS:

Mix ratio A:B	Gel time 100g (minutes)	Shore Hardness	Mixed Viscosity (cps)
2.0 : 1.0	273	70D	8040
1.5 : 1.0	222	75D	7000
1.0 : 1.0	169	68D	5220
0.5 : 1.0	212	60A	3820

To the best of our knowledge, the information contained herein is accurate. However, STAR TECHNOLOGY, Inc., does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any material is the sole responsibility of the user. The information contained herein is considered typical properties and is not intended to be used as specifications for our products. This information is offered solely to assist purchaser in selecting the appropriate products for purchaser's own testing. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein and in the material safety data sheet, we cannot guarantee that these are the only hazards that exist. Repeated and prolonged exposure to epoxy resins can cause sensitization or other allergic responses.



STAR Technology

FORMULATING • INNOVATIVE • SOLUTIONS

ER2109

Two Part Epoxy Adhesive

APPLICATION PROCEDURES

Carefully weigh out appropriate amounts of resin and hardener into a clean mixing container and thoroughly mix until all streaks and striations are gone. Scrape the sides and bottom frequently to ensure complete mixing.

For 1# and 2# kits, add all of Part B to Part A and mix thoroughly.

CAUTION: Unmixed compound from the sides or bottom of the container can cause soft spots or uncured areas in the completed piece. To prevent this, transfer the entire mixed contents to a second clean container and remix for a short time before using.

PRECAUTIONS

For industrial use only. Keep away from children.

Refer to the Material Safety Data Sheets (MSDS forms) pertaining to this product before using.

Avoid contact with skin or eyes. In the event of an eye splash or contact, immediately flush with cold water for 15 minutes and contact a physician. If skin contact occurs, wash with mild soap and water. The wearing of safety glasses with side shields and impervious gloves is recommended.

RESIN AND HARDENER WARNING STATEMENT

May cause allergic skin reaction. Avoid all contact with skin, eyes, and clothing. Wash thoroughly after handling.

To the best of our knowledge, the information contained herein is accurate. However, STAR TECHNOLOGY, Inc., does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any material is the sole responsibility of the user. The information contained herein is considered typical properties and is not intended to be used as specifications for our products. This information is offered solely to assist purchaser in selecting the appropriate products for purchaser's own testing. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein and in the material safety data sheet, we cannot guarantee that these are the only hazards that exist. Repeated and prolonged exposure to epoxy resins can cause sensitization or other allergic responses.